


## Chase & Sons® L1080GR Shielding Tape

**CONSTRUCTION**      0.00075 Polyester Film  
                                 0.00035 Aluminum Foil



**DESCRIPTION**      Chase & Sons® L1080GR is a laminate of polyester film and aluminum foil intended for use as a shielding tape.

### TECHNICAL DATA

Property	US Customary	Metric	Test Method
Thickness	0.00120"	0.030 mm	ASTM D374
Weight	9.4 lb/csy	51.0 g/m <sup>2</sup>	Measured
Yield	10.6 sy/lb 0.87 lbs/mft @1" wide	19.6 m <sup>2</sup> /kg 0.51 kg/km @10mm wide	Calculated
Tensile Strength	21000 psi	145 MPa	Calculated
Break Strength	25 piw	44 N/cm	ASTM D882
Elongation	80%	80%	ASTM D882
Density	0.96 oz/cu in	1.68 g/cm <sup>3</sup>	Calculated

### GENERAL PROPERTIES

Color	Green
Core	3" or 6" , Paper
Standard Pad Put-up	3"x12, 15, 18" or 6"x18"
Traverse Pad Put-up	3"x12"x3, 6, 12"

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.